



SABMA Code	Enertec Item Code	Capacity 20/hr Rate	CCA En (-18°C)	Res Cap Minutes	Length mm	Width mm	Height mm	Mass kg	Terminal Layout
------------	-------------------	---------------------	----------------	-----------------	-----------	----------	-----------	---------	-----------------

U.P.S ENERTEC SMF RANGE (Sealed Premium Maintenance Free)

NS40 Slim line	11BAT615-VAL	35	300	59	187	127	227	10.1	LHP Tapered
NS40 Slim line	11BAT616-VAL	35	300	59	187	127	227	10.1	RHP Tapered
35 Amp/hr Squat	11BAT618-VAL	35	330	60	207	175	175	10.33	RHP Tapered
44 Amp/hr Squat	11BAT619HC-VAL	44	440	75	207	175	175	11.47	RHP Tapered
NS70 (60Amp/hr)	11BAT638-VAL	68	450	95	261	175	220	15.70	LHP Tapered
NS70 (60Amp/hr)	11BAT639-VAL	68	450	95	261	175	220	15.70	RHP Tapered
NS70	11BAT638HC-VAL	70	550	115	261	172	220	15.59	LHP Tapered
NS70	11BAT639HC-VAL	70	550	115	261	172	220	15.59	RHP Tapered

U.P.S DISCOVER VRLA AGM RANGE (12 YEAR DESIGN LIFE)

12v4.5	18BAT12V4/5A-DIS	4.5	-	-	90	70	101	1.72	Wide
12v7.2	18BAT12V7/2A-DIS	7.2	-	-	151	65	95	2.43	Wide
12v12	18BAT12V12A-DIS	12	-	-	151	98	95	3.9	Wide
12v18	18BAT12V18A-DIS	18	-	-	181	77	167	5.7	Screw In
12v24	18BAT12V24A-DIS	24	-	-	166	175	125	8.6	Screw In

FORBATT SLA VALUE REGULATED (5 YEAR DESIGN ON FLOAT)

12V4.5	18BAT-12V4/5A-FB	4.5	12	90	70	101	107	1.72	Wide
12V7.2	18BAT-12V7/2A-FB	7.2	12	151	65	95	101	2.43	Wide
12V12	18BAT-12V12A-FB	12	12	151	98	95	101	3.9	Wide
12V18	18BAT-12V18A-FB	17	12	181	77	167	167	5.7	Screw In
12V24	18BAT-12V24A-FB	24	12	166	175	125	125	8.6	Screw In

ENERTEC MARINE DEEP CYCLE

100 Amp/hr Deep Cycle	13BAT-M27-VAL	100	750	180	306	173	227	23	LHP Tapered
-----------------------	---------------	-----	-----	-----	-----	-----	-----	----	-------------

DISCOVER EV TRACTION DRY CELL 12 VOLT MONOBLOCKS

EV27A-A Traction	12BAT27A-A-DIS	100	-	-	308	172	232	29	AM (M8)
EV31A-A Traction	12BAT31A-A-DIS	115	-	-	330	172	236	33	AM (M8)